

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

AMENDMENT TO THE CLAIMS:

1. (Currently amended) A tamper-detection-information embedding apparatus for embedding predetermined information for tamper detection in a digital image signal, said apparatus comprising:

a band division means for dividing said portion operable to divide the digital image signal into a plurality of frequency bands;

an authentication data generation means for generating portion operable to generate a pseudo-random number series by using predetermined key data, and generating to generate authentication data from the pseudo-random number series;

a key data embedding means for embedding said portion operable to embed the key data in transform coefficients of a lowest frequency band (hereinafter, referred to as MRA) among said the plurality of frequency bands;

an authentication data embedding means for embedding said portion operable to embed the authentication data in transform coefficients of the frequency bands exclusive of said the MRA (hereinafter, referred to as MRR) among said the plurality of frequency bands; and

a band synthesis means for reconstructing portion operable to reconstruct the digital image signal in which the information has been embedded by using said the MRA and said the MRR to which data embedding processing is subjected.

2. (Currently amended) The tamper-detection-information embedding apparatus according to claim 1, ~~wherein~~

wherein a set value T (~~T is a positive integer~~) and a set value m (~~m is an integer not more than T~~) are predetermined and q is predetermined as a value obtained by dividing a transform coefficient by a predetermined quantization step size, and

wherein said authentication data embedding means portion embeds said the authentication data in each transform coefficient of said the MRR by comparing an absolute value of said the

transform coefficient with ~~said the~~ set value T, and if the absolute value is less than ~~said the~~ set value T, setting the transform coefficient to ~~said the~~ set value +m or -m depending on a bit value of ~~said the~~ authentication data to be embedded, and if the absolute value is not less than ~~said the~~ set value T, setting the transform coefficient to an even or odd integer nearest to ~~said the~~ value q depending on the bit value of ~~said the~~ authentication data to be ~~embedded~~. embedded, and
wherein T is a positive integer and m is an integer not more than T.

3. (Currently amended) A tamper detecting apparatus for detecting tamper with a digital image based on tamper-detection-information embedded by a specific apparatus in a digital image signal, said tamper detecting apparatus comprising:

a band division means for dividing said portion operable to divide the digital image signal into a plurality of frequency bands;

a key data extraction means for extracting portion operable to extract key data embedded by said the specific apparatus from transform coefficients of a lowest frequency band (hereinafter, referred to as MRA) among said the plurality of frequency bands;

an authentication data generation means for generating portion operable to generate a pseudo-random number series by using said the key data, and generating to generate authentication data from the pseudo-random number series;

an embedded information extraction means for extracting portion operable to extract embedded information embedded based on said the key data by said the specific apparatus from transform coefficients of the frequency bands exclusive of said the MRA (hereinafter, referred to as MRR) among said the plurality of frequency bands; and

a tamper determination means for comparing said portion operable to compare the embedded information with said the authentication data for verification and determining to determine whether said the digital image has been tampered with.

4. (Currently amended) The tamper detecting apparatus according to claim 3, wherein said tamper determination ~~means~~ portion comprises:

a block division ~~means for dividing~~ portion operable to divide the digital image into a plurality of unit blocks each composed of a predetermined number of pixels;

a regional embedded information read ~~means for reading~~ portion operable to read, for each of ~~said the~~ the unit blocks, embedded information embedded in the transform coefficients of ~~said the~~ the MRR that represents the same spatial region as the unit block, serially from all of ~~said the~~ the embedded information extracted by said embedded information extraction ~~means~~ portion;

a regional authentication data read ~~means for reading~~ portion operable to read, for each of ~~said the~~ the unit blocks, authentication data corresponding in position to ~~said the~~ the embedded information serially read by said regional embedded information read ~~means~~ portion, serially from all of ~~said the~~ the authentication data generated by said authentication data generation ~~means~~ portion; and

a block-tamper determination ~~means for comparing~~ ~~said~~ portion operable to compare the embedded information serially read with ~~said the~~ the authentication data serially read and ~~determining to~~ determine, for each of ~~said the~~ the unit blocks, whether ~~said the~~ the digital image has been tampered with.

5. (Currently amended) The tamper detecting apparatus according to claim 3, ~~wherein~~ wherein a set value T (~~T is a positive integer~~) is predetermined and q is predetermined as a value obtained by dividing a transform coefficient ~~is~~ by a predetermined quantization step size and then rounding off the result, and

wherein said embedded information extraction ~~means~~ portion extracts ~~said the~~ the embedded information from each transform coefficient of ~~said the~~ the MRR by comparing an absolute value of ~~said the~~ the transform coefficient with ~~said the~~ the set value T, and if the absolute value is less than ~~said the~~ the set value T, determining whether a value of the transform coefficient is positive or negative and extracting a bit value of embedded information embedded in the transform coefficient based on the determination, and if the absolute value is not less than ~~said the~~ the set value T, determining whether ~~said the~~ the value q is even or odd and extracting a bit value of embedded information embedded in the transform coefficient based on the ~~determination~~; determination, and

wherein T is a positive integer.

6. (Currently amended) The tamper detecting apparatus according to claim 4, ~~wherein~~
wherein a set value T (~~T is a positive integer~~) is predetermined and q is predetermined as a
value obtained by dividing a transform coefficient by a predetermined quantization step size and then
rounding off the result, ~~and~~

wherein said embedded information extraction ~~means portion~~ extracts ~~said the~~ embedded
information from each transform coefficient of ~~said the~~ MRR by comparing an absolute value of ~~said~~
the transform coefficient with ~~said the~~ set value T, and if the absolute value is less than ~~said the~~ set
value T, determining whether a value of the transform coefficient is positive or negative and
extracting a bit value of embedded information embedded in the transform coefficient based on the
determination, and if the absolute value is not less than ~~said the~~ set value T, determining whether
~~said the~~ value q is even or odd and extracting a bit value of embedded information embedded in the
transform coefficient based on the ~~determination~~; determination, and
wherein T is a positive integer.

7. (Currently amended) A tamper-detection-information embedding method of embedding
predetermined information for tamper detection in a digital image signal, said method comprising:
~~a step of~~ dividing ~~said the~~ digital image signal into a plurality of frequency bands;
~~a step of~~ generating a pseudo-random number series by using predetermined key data, and
generating authentication data from the pseudo-random number series;
~~a step of~~ embedding ~~said the~~ key data in transform coefficients of a lowest frequency band
(hereinafter, referred to as MRA) among ~~said the~~ plurality of frequency bands;
~~a step of~~ embedding ~~said the~~ authentication data in transform coefficients of the frequency
bands exclusive of ~~said the~~ MRA (hereinafter, referred to as MRR) among ~~said the~~ plurality of
frequency bands; and
~~a step of~~ reconstructing the digital image signal in which the information has been embedded
by using ~~said the~~ MRA and ~~said the~~ MRR to which data embedding processing is subjected.

8. (Currently amended) The tamper-detection-information embedding method according to claim 7, ~~wherein~~

~~wherein~~ a set value T (~~T is a positive integer~~) and a set value m (~~m is an integer not more than T~~) are predetermined and q is predetermined as a value obtained by dividing a transform coefficient by a predetermined quantization step size, ~~and~~

~~said step of wherein~~ embedding authentication data ~~includes:~~ includes

~~a step of~~ comparing an absolute value of ~~said the~~ transform coefficient with ~~said the~~ set value T;

~~a step of~~ setting the transform coefficient to ~~said the~~ set value +m or -m depending on a bit value of ~~said the~~ authentication data to be embedded if the absolute value is less than ~~said the~~ set value T; T, and

~~a step of~~ setting the transform coefficient to an even or odd integer nearest to ~~said the~~ value q depending on the bit value of ~~said the~~ authentication data to be embedded if the absolute value is not less than ~~said the~~ set value T; T, and

wherein T is a positive integer and m is an integer not more than T.

9. (Currently amended) A tamper detecting method of detecting tamper with a digital image based on tamper-detection-information embedded by a specific apparatus in a digital image signal, said method comprising:

~~a step of~~ dividing ~~said the~~ digital image signal into a plurality of frequency bands;

~~a step of~~ extracting key data embedded by ~~said the~~ specific apparatus from transform coefficients of a lowest frequency band (hereinafter, referred to as MRA) among ~~said the~~ plurality of frequency bands;

~~a step of~~ generating a pseudo-random number series by using ~~said the~~ key data, and generating authentication data from the pseudo-random number series;

~~a step of~~ extracting embedded information embedded based on ~~said the~~ key data by ~~said the~~ specific apparatus from transform coefficients of the frequency bands exclusive of ~~said the~~ MRA

(hereinafter, referred to as MRR) among ~~said~~ the plurality of frequency bands; and

~~a step of~~ comparing ~~said~~ the embedded information with ~~said~~ the authentication data for verification and determining whether ~~said~~ the digital image has been tampered with.

10. (Currently amended) The tamper detecting method according to claim 9, ~~wherein~~ further comprising

~~said step of determining tamper comprises:~~

~~a step of~~ dividing the digital image into a plurality of unit blocks each composed of a predetermined number of pixels;

~~a step of~~ reading, for each of ~~said~~ the unit blocks, embedded information embedded in the transform coefficients of ~~said~~ the MRR that represents the same spatial region as the unit block, serially from all of ~~said~~ the embedded information;

~~a step of~~ reading, for each of ~~said~~ the unit blocks, authentication data corresponding in position to ~~said~~ the embedded information serially read, serially from all of ~~said~~ the authentication data; and

~~a step of~~ comparing a series of ~~said~~ the embedded information serially read with a series of ~~said~~ the authentication data serially read and determining, for each of ~~said~~ the unit blocks, whether ~~said~~ the digital image has been tampered with.

11. (Currently amended) The tamper detecting method according to claim 9, ~~wherein~~ wherein a set value T (~~T is a positive integer~~) is predetermined and q is predetermined as a value obtained by dividing a transform coefficient by a predetermined quantization step size and then rounding off the result, ~~and~~

wherein ~~said step of extracting embedded information includes:~~ includes

~~a step of~~ comparing an absolute value of ~~said~~ the transform coefficient with ~~said~~ the set value T ; T

~~a step of~~ determining whether a value of the transform coefficient is positive or negative if the absolute value is less than ~~said~~ the set value T , and extracting a bit value of embedded

information embedded in the transform coefficient based on the ~~determination;~~ determination, and
a step of determining whether ~~said the~~ value q is even or odd if the absolute value is not less
than ~~said the~~ set value T, and extracting a bit value of embedded information embedded in the
transform coefficient based on the ~~determination.~~ determination, and
wherein T is a positive integer.

12. (Currently amended) The tamper detecting method according to claim 10, ~~wherein~~
wherein a set value T (~~T is a positive integer~~) is predetermined and q is predetermined as a
value obtained by dividing a transform coefficient by a predetermined quantization step size and then
rounding off the result, and

wherein said ~~step of~~ extracting embedded information ~~includes;~~ includes
a step of comparing an absolute value of ~~said the~~ transform coefficient with ~~said the~~ set value
T; T,

a step of determining whether a value of the transform coefficient is positive or negative if
the absolute value is less than ~~said the~~ set value T, and extracting a bit value of embedded
information embedded in the transform coefficient based on the ~~determination;~~ determination, and
a step of determining whether ~~said the~~ value q is even or odd if the absolute value is not less
than ~~said the~~ set value T, and extracting a bit value of embedded information embedded in the
transform coefficient based on the ~~determination.~~ determination, and
wherein T is a positive integer.

13. (Currently amended) A recording medium on which a program having computer device
readable instructions to be run on a computer device is recorded for carrying out a tamper-detection-
information embedding method of embedding predetermined information for tamper detection in a
digital image signal, the ~~method comprising the steps of~~ computer device readable instructions
including instructions capable of instructing a computer device to perform the method comprising:
dividing ~~said the~~ digital image signal into a plurality of frequency bands;
generating a pseudo-random number series by using predetermined key data, and generating

authentication data from the pseudo-random number series;

embedding ~~said the~~ key data in transform coefficients of a lowest frequency band (hereinafter, referred to as MRA) among ~~said the~~ plurality of frequency bands;

embedding ~~said the~~ authentication data in transform coefficients of the frequency bands exclusive of ~~said the~~ MRA (hereinafter, referred to as MRR) among ~~said the~~ plurality of frequency bands; and

reconstructing the digital image signal in which the information has been embedded by using ~~said the~~ MRA and ~~said the~~ MRR to which data embedding processing is subjected.

14. (Currently amended) The recording medium according to claim 13, ~~wherein~~
~~wherein~~ a set value T (~~T is a positive integer~~) and a set value m (~~m is an integer not more than T~~) are predetermined and q is predetermined as a value obtained by dividing a transform coefficient by a predetermined quantization step size, ~~and~~

~~wherein~~ said ~~step of~~ embedding authentication data includes the steps of:

comparing an absolute value of ~~said the~~ transform coefficient with ~~said the~~ set value T ; T ,

setting the transform coefficient to ~~said the~~ set value $+m$ or $-m$ depending on a bit value of ~~said the~~ authentication data to be embedded if the absolute value is less than ~~said the~~ set value T ; T ,
and

setting the transform coefficient to an even or odd integer nearest to ~~said the~~ value q depending on the bit value of ~~said the~~ authentication data to be embedded if the absolute value is not less than ~~said the~~ set value T ; T , and

~~wherein~~ T is a positive integer and m is an integer not more than T .

15. (Currently amended) A recording medium on which a program having computer device readable instructions to be run on a computer device is recorded for carrying out a tamper detecting method of detecting tamper with a digital image based on tamper-detection-information embedded by a specific apparatus in a digital image signal, ~~the method comprising the steps of~~ computer device readable instructions including instructions capable of instructing a computer device to perform the

method comprising:

dividing ~~said~~ the digital image signal into a plurality of frequency bands;

extracting key data embedded by ~~said~~ the specific apparatus from transform coefficients of a lowest frequency band (hereinafter, referred to as MRA) among ~~said~~ the plurality of frequency bands;

generating a pseudo-random number series by using ~~said~~ the key data, and generating authentication data from the pseudo-random number series;

extracting embedded information embedded based on ~~said~~ the key data by ~~said~~ the specific apparatus from transform coefficients of the frequency bands exclusive of ~~said~~ the MRA (hereinafter, referred to as MRR) among ~~said~~ the plurality of frequency bands; and

comparing ~~said~~ the embedded information with ~~said~~ the authentication data for verification and determining whether ~~said~~ the digital image has been tampered with.

16. (Currently amended) The recording medium according to claim 15, wherein ~~said step of determining tamper comprises~~ the computer device readable instructions include instructions capable of instructing a computer device to perform the method further comprising:

dividing the digital image into a plurality of unit blocks each composed of a predetermined number of pixels;

reading, for each of ~~said~~ the unit blocks, embedded information embedded in the transform coefficients of ~~said~~ the MRR that represents the same spatial region as the unit block, serially from all of ~~said~~ the embedded information;

reading, for each of ~~said~~ the unit blocks, authentication data corresponding in position to ~~said~~ the embedded information serially read, serially from all of ~~said~~ the authentication data; and

comparing a series of ~~said~~ the embedded information serially read with a series of ~~said~~ the authentication data serially read and determining, for each of ~~said~~ the unit blocks, whether ~~said~~ the digital image has been tampered with.

17. (Currently amended) The recording medium according to claim 15, ~~wherein~~
wherein a set value T (~~T is a positive integer~~) is predetermined and q is predetermined as a
value obtained by dividing a transform coefficient is divided by a predetermined quantization step
size and then rounding off the result, ~~and~~

wherein said ~~step of~~ extracting embedded information includes ~~the steps of:~~

comparing an absolute value of ~~said~~ the transform coefficient with ~~said~~ the set value T; T,
determining whether a value of the transform coefficient is positive or negative if the absolute
value is less than ~~said~~ the set value T, and extracting a bit value of embedded information embedded
in the transform coefficient based on the ~~determination;~~ determination, and

determining whether ~~said~~ the value q is even or odd if the absolute value is not less than ~~said~~
the set value T, and extracting a bit value of embedded information embedded in the transform
coefficient based on the ~~determination.~~ determination, and

wherein T is a positive integer.

18. (Currently amended) The recording medium according to claim 16, ~~wherein~~
wherein a set value T (~~T is a positive integer~~) is predetermined and q is predetermined as a
value obtained by dividing a transform coefficient by a predetermined quantization step size and then
rounding off the result, ~~and~~

wherein said ~~step of~~ extracting embedded information includes ~~the steps of:~~

comparing an absolute value of ~~said~~ the transform coefficient with ~~said~~ the set value T; T,
determining whether a value of the transform coefficient is positive or negative if the absolute
value is less than ~~said~~ the set value T, and extracting a bit value of embedded information embedded
in the transform coefficient based on the ~~determination;~~ determination, and

determining whether ~~said~~ the value q is even or odd if the absolute value is not less than ~~said~~
the set value T, and extracting a bit value of embedded information embedded in the transform
coefficient based on the ~~determination.~~ determination, and

wherein T is a positive integer.